

EMAX - trójfazowe silniki klasy BL - samolotowe

Typ silnika	RMP/V obroty/min/V	Ilość celi LiPo	Średnica wału (mm)	Zalecane śmigło	Maksymalna moc	Maksymalny ciąg	Masa silnika	Masa modelu
BL1806	1650	2-3S	3	6"-7"	126W	260g	18g	200g
BL1812	1800	2-3S	3	7"-8"	159W	430g	28g	300g
BL2205	1650	2s	3	5"-8"	88W	369g	34g	220-330
BL2210/25	1560	2-3S	3	7"-8"	227W	730g	45g	200 - 700
BL2210/30	1300	2-3S	3	8"-9"	214W	800g	45g	200 - 750
BL2215/25	950	2-3S	3	9"-10"	208W	950g	59g	300- 900
BL2215/20	1200	2-3S	3	9"-10"	309W	1200g	59g	400 - 1150
BL2220/07	1200	2-3S	4	10"-11"	391W	1400g	85g	600-1400
BL2220/08	1050	2-3S	4	10"-11"	378W	1280g	85g	600-1400
BL2220/09	850	2-3S	4	11"-12"	239W	1150g	85g	400-1200
BL2220/10	930	2-3S	4	11"-12"	302W	1220g	85g	400-1300
BL2810	1100	3S	5	10"-11"	378W	1320g	86g	600 - 1400
BL2815	920	3S	5	11"-12"	391W	1550g	112g	600 - 1700
BL2820	919	3-4s	5	11"-12"	991W	2105g	144g	600 - 1600
BL2826	850	4s	5	12"-13"	1025W	2650g	182g	2000-3200
BL2832	805	4s	5	13"-14"	1159W	3150g	210g	2000-4000
BL3526/04	860	5s	5	13"-14"	1302W	3000g	250g	2500-3000
BL3526/05	685	5s	5	13"-14"	1302W	2800g	250g	2500-3000
BL4020	522	5-6s	8	12"-13"	1512W	4314g	248g	2000-4000
BL4030	385	5-6s	8	14"-16"	1386W	5300g	325g	3000-6000
BL5335	230	10s	8	20"-22"	3276W	8600g	668g	5000-10000
BL5345	195	10s	8	22"	3780W	12000g	790g	12000g

EMAX - trójfazowe silniki klasy BL - śmigłowcowe

Typ silnika	RMP/V obroty/min/V	Ilość celi LiPo	Średnica wału (mm)	Maksymalna moc	Przeznaczenie silnika	Masa silnika
HL2010/06	4050	2-3S	2,3		Śmigłowce klasy 200-400	38g
HL2010/04	5000	2-3S				
HL2215	3700	3-4s	2.3/3.17	504W	Śmigłowce klasy 450	62g
HL2832	960	4s	5	720W	Śmigłowce klasy 500	232g